



### APPLICATIONS:

Carbon Dioxide is the trusted "clean agent" that gives fast and safe protection for sensitive equipment. It is the right choice for virtually all industrial hazards where flammable liquids, gases and energized electrical fires may be present. These extinguishers are effective on class B and C fires.

### SIZE:

Available in a range of sizes from 5 to 20-pound capacity. When very large hazards require additional protection, wheeled extinguishers are also available.

### OPERATION AND AGENT:

Badger carbon dioxide fire extinguishers are easy to use. Our rugged, easy-squeeze hand-operated, metal valve assembly allows for quick response to a fire. Liquid carbon dioxide, under pressure, is discharged as particles of "snow" and leaves no messy residue.



- Features a lightweight alloy aluminum cylinder.
- Attractive epoxy coating effective against corrosion.
- Easy-squeeze hand-operated, forged brass nickel/chrome plated valves.
- Long-lasting nickel/chrome plated brass valve with stainless steel handle and lever.
- O-ring seal. Straight-thread design.
- Maximum performance at both high and low temperature extremes.
- Extinguisher resists dents and punctures.
- Rugged, stainless steel hose and horn bracket band.
- Lengthy 5-year interval between hydrotests.





MODEL NO	BSV	B10V	B15V	B20V
NOMINAL CAPACITY LBS. (KG)	5 (2.27)	10 (4.54)	15 (6.8)	20 (9.07)
U/L RATING	5B.C	10B.C	10B.C	10B.C
AGENT	CO <sub>2</sub>	CO <sub>2</sub>	CO <sub>2</sub>	CO <sub>2</sub>
ITEM PART NO.	21111	21106	21103	21096
VALVE MATERIAL	BRASS	BRASS	BRASS	BRASS
SHELL MATERIAL	ALUM.	ALUM.	ALUM.	ALUM.
SHIPPING WT. LBS. (KG.)	15 (6.8)	30 (13.6)	40 (18.1)	51 (23.1)
OPERATING PRESSURE	—	—	—	—
TEMP. RANGE (F)	-40° TO 120°	-40° TO 120°	-40° TO 120°	-40° TO 120°
DISCHARGE TIME (SEC.)	9.0	10.0	14.0	17.0
RANGE FEET (METERS)	3-8 (0.9-2.4)	3-8 (0.9-2.4)	3-8 (0.9-2.4)	3-8 (0.9-2.4)
UNIT HEIGHT IN. (CM)	17 (43.2)	19.375 (49.2)	26 (66.0)	26 (66.0)
UNIT WIDTH IN. (CM)	8.5 (21.6)	10.875 (27.6)	10.875 (27.6)	12 (30.5)
SHELL DIAMETER IN. (CM)	5.25 (13.34)	6.875 (17.46)	6.875 (17.46)	8 (20.32)
USCG APPROVAL	YES	YES	YES	NO
USCG BRACKET	CALL FOR INFORMATION			

Distributed by:

Fire Extinguisher Co., Inc.

1-888-ILL-FIRE